

ENNIS-FLINT 2000 EX PROPANE HEAT TORCH

INDUSTRIAL STRENGTH
WITH SAFETY IN MIND



ENNIS-FLINT
The Mark of Traffic Safety®



ENNIS-FLINT® 2000 EX PROPANE HEAT TORCH

With Patented Cold Burning Nozzle -
Safety is what makes the 2000 EX stand
out from all other heat torches.



With its patented cold burning nozzle, the 2000 EX propane heat torch is safe and comfortable to use even in the most extreme temperatures. This UL-listed heat torch features an electric ignition, hand guard, deadman trigger, and an automatic POL valve for maximum safety.

The 2000 EX is specially designed for installing preformed thermoplastic pavement markings and adhesives. It can also be used for removal of paint, drying loop detector grooves, removal of cold plastic and temporary tape, shrinking plastic for wrapping, drying road surfaces and for melting snow or ice.

The 2000 EX measures 37" overall including the 29" extension. The fan-shaped nozzle ensures even heating when applying preformed thermoplastic in any

season, but especially in windy, wet spring months. The swivel hose connector prevents kinks and twisting. The 2000 EX consumes only 8 pounds of propane per hour of continuous use.

Using the 2000 EX to apply preformed thermoplastic pavement markings will reduce the likelihood that the surface glass beads will sink too much when heating. Other heat torches may put out so much concentrated heat in one spot that it is virtually impossible to control the embedment of the surface glass beads which can result in lower initial retroreflectivity.

2000 EX TROLLEY

For additional convenience, consider the optional cylinder trolley. It provides an easy way to transport heat torches and propane cylinders.



Lightweight and sturdy, the trolley holds any 20-40 lb. propane cylinder. For large jobs, it can significantly reduce operator fatigue and increase safety.

PERFORMANCE-BASED FEATURES

- Standard 29" extension from the handle.
- Consumes only 8 pounds of propane per hour of continuous use.
- Produces a minimum of 200,000 BTU
- The hose is 25' long with 360° swivel joint that prevents kinking and twisting.
- The flame is steady and fan shaped which reduces scorching and splattering of material.
- The shape of the nozzle ensures an even heating of the material.
- The adjustable pressure valve allows you to control the amount of propane used by the torch.
- The 90 degree rotating nozzle is ergonomically designed with comfort in mind to reduce user fatigue.

AUTOMATIC SAFETY POL VALVE

The automatic safety POL valve on regulator cuts off fuel supply in case the hose gets cut or starts leaking.

HAND GUARD

The hand guard prevents the trigger from being pressed accidentally.

DEADMAN TRIGGER

The deadman trigger device extinguishes the flame when the trigger is released.

PIEZO ELECTRIC IGNITION

The Piezo electric ignition eliminates pilot flame concerns. The automatic ignition system means that the heat torch is only operational when the trigger is pressed, therefore, eliminating safety and productivity concerns with having an open flame system.

COLD BURNING NOZZLE

The exclusive cold burning nozzle allows the propane gas to burn outside the nozzle so the nozzle remains cool.

UL LISTED

The UL-Listed symbol on each 2000 EX Heat Torch ensures that its safety features meet recognized national and international safety standards.

Item # 530108 (cylinder not included)