


STIMSONITE MODEL 201

The Lens Cradle With C40 Replaceable Lens

PRODUCT DATA

Product Type: The Lens Cradle
Design: 5.00" x 3.00" x 0.70" (12.70 cm x 7.62 cm x 1.78 cm)
Installed Height: 0.10" (0.25 cm)
Weight: 2.12 oz. (60 grams)
Material: Polycarbonate plastic
Specification: Meets ASTM D 4280 (w/C40 lens)
Effective Date: 2016



Product Description:

Raised pavement markers are a safety device used on roads to improve delineation and increase preview time, particularly under wet conditions, and have been shown to decrease crash rates on highways with raised pavement marker center lines by approximately 0.5 crashed per million vehicle miles.

Raised pavement markers play an important safety function on roads, communicating both the travel path for short and long range vehicle operation.

Features a polycarbonate casting and a replaceable C40 lens that has an ABS plastic body and coated polycarbonate lenses.

The roadway is recessed and two Lens Cradles are placed on opposite sides of the slot and applied using an approved epoxy that meets AASHTO M237 Type IV. The replacement cycle for castings is approximately ten years while the lens replacement cycle is 2-4 years depending on the road's ADT.

Product Advantages:

- Polycarbonate casting is safer due to its lightweight design
- Dual tab design places the casting at the optimal depth to prevent snowplow blade hits while maintaining superior wet night reflectivity
- Abrasion resistant coating provides enhanced retained reflectivity
- Advanced optics deliver high reflectivity and durability
- Initial SI values engineered to at least double ASTM standards
- Recommended for high ADT and high intensity conditions

Packaging:

Available in 50 piece boxes per color and casting style.

Other:

The following lens colors are available: white, yellow, red, blue, green, and fluorescent orange. Markers are available as a one-way marker with one lens and one plug, a two-way marker with two lenses of the same color, or a two-way marker with two different colored lenses.

Physical Characteristics Of C40 Lens:

Slope Of Lens:	35 degrees to base	
Lens Face:	1.93 sq.in. (12.48 sq. cm.)	
Compressive Strength Requirement: (ASTM D 4280)	> 6,000 lbs. (2,722 kg)	
Coefficient Of Luminous Intensity (mcd/lx): (ASTM D 4280)	<u>0 Degrees</u>	<u>20 Degrees</u>
White	279	112
Yellow	167	67
Red	70	28
Green	93	37
Blue	26	10
Specific Intensity (cd/fc): (ASTM D 4280)	<u>0 Degrees</u>	<u>20 Degrees</u>
White	3.0	1.2
Yellow	1.8	0.72
Red	0.75	0.30
Green	1.0	0.4
Blue	0.28	0.11
Coefficient Of Luminous Intensity After Abrasion Resistance Testing (mcd/lx): (ASTM D 4280)	<u>0 Degrees</u>	<u>20 Degrees</u>
White	140	56
Yellow	84	34
Red	35	14
Green	47	19
Blue	13	5
Specific Intensity After Abrasion Resistance Testing (cd/fc): (ASTM D 4280)	<u>0 Degrees</u>	<u>20 Degrees</u>
White	1.5	0.60
Yellow	0.90	0.36
Red	0.38	0.15
Green	0.50	0.20
Blue	0.14	0.06

The product data offered herein is, to the best of our knowledge, true and accurate, but all recommendations are made without warranty, expressed or implied. Because the conditions of use are beyond our control, neither Ennis-Flint nor its agents shall be liable for any injury, loss or damage, direct or consequential, arising from the use or the inability to use the product described herein. As Ennis-Flint has neither control over the installation of product described herein nor control of the environmental factors the installed markings are subjected to, there is no guarantee as to the durability or the retroreflective properties of any marking system applied. No person is authorized to make any statement or recommendation not contained in the Product Data, and any such statement or recommendation, if made, shall not bind the Corporation. Further, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents, and no license under the claims of any patent is either implied or granted.



ENNIS-FLINT
A Traffic Safety Solutions Company

800.331.8118

sales@ennisflint.com

www.ennisflint.com

© Ennis-Flint All Rights Reserved